



10/531668
PCT/GE 03/004280
Rec'd PCT/PTO 15 APR 2005

INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 800

REC'D 18 NOV 2003

WIPO PGT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


BEST AVAILABLE COPY

Signed

Le Behen


Dated

12 November 2003



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference P451569

2. Patent application number 0223959.8
(The Patent Office will fill in this part) 15 OCT 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)
Hi-Lex Cable System Company Limited,
Baglan Energy Park,
Port Talbot SA12 7YL.

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation England & Wales

8484529001

4. Title of the invention

ANCHORING AN ELONGATE MEMBER

5. Name of your agent (if you have one) Urquhart-Dykes & Lord

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Alexandra House
1 Alexandra Road
SWANSEA
SA1 5ED
United Kingdom

Patents ADP number (if you know it)

1644005

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
--	---------	--	-------------------------------------

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)
---	-------------------------------	-------------------------------------

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	0
Description	5
Claim(s)	2
Abstract	1
Drawing(s)	4 <i>14</i>

10. If you are also filing any of the following, state how many against each item.

Priority documents	0
Translations of priority documents	0
Statement of inventorship and right to grant of a patent (<i>Patents Form 7/77</i>)	0
Request for preliminary examination and search (<i>Patents Form 9/77</i>)	1 <input checked="" type="checkbox"/>
Request for substantive examination (<i>Patents Form 10/77</i>)	0
Any other documents (<i>please specify</i>)	0

11. I/We request the grant of a patent on the basis of this application

Signature

Date 15 October 2002

Christopher Dykes & Co

12. Name and daytime telephone number of person to contact in the United Kingdom

01792 474327

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first get written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 5005
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Anchoring an Elongate Member

This invention relates to apparatus for use in anchoring an elongate member to another member and, more particularly, but not necessarily exclusively, to an abutment for use in anchoring a flexible control cable to fixed members of the chassis or bodywork of a vehicle.

A "push-pull" cable is a device for translating a push/pull movement at one location to a push/pull movement (in the same or any different direction) at a different location, often for control purposes, and such a cable comprises a flexible conduit in which a control wire is slidable to perform the desired function. In order for the relative movement of the control wire and the conduit to take place in a controlled manner for the reliable operation of, for example, a clutch or gearbox mechanism or throttle of a motor vehicle, it is necessary that each end of the conduit be anchored, for example to the body of a vehicle. In particular, the practice has developed of anchoring an end of the conduit to an opening in a bracket or bulkhead across which the control cable passes.

In general, such anchorage is achieved by means of a bracket or similar fixed member, having a generally U-shaped slot therein for receiving an abutment attached to a cable. The abutment is located in the slot of the bracket and fixed therein by some means so as to resist withdrawal of the abutment from the slot and also axial movement of the abutment relative to the slot. Conventional fixing means for this purpose have meant that the abutment must be presented to the bracket from a particular direction and orientation, so that corresponding elements of the fixing means on the abutment and the bracket are precisely located relative to each other. In addition, many conventional abutment arrangements tend to have a somewhat complex structure which is relatively difficult and time-consuming to assemble.

In particular in the motor industry, there is a constant requirement to simplify and speed up the vehicle assembly process and it is therefore an object of the present invention to provide apparatus for use in quickly, easily and reliably anchoring an elongate member to another member.

In accordance with the present invention, there is provided an anchoring device which is suitable for anchoring an elongate member to a fixed member having a slot leading to an edge thereof, the anchoring device comprising a sleeve which is fixable coaxially around said elongate member and which is provided with a circumferential groove, the axial length of which is sufficient to accommodate the thickness of the fixed member at said slot, the outer diameter of the groove being less than the inner diameter of the slot, the anchoring device further comprising a collar member which is carried by, and axially moveable along, said sleeve, said collar member having a leading edge which extends into said groove when the anchoring device is located within said slot, to effectively increase the diameter of said groove and prevent said anchoring device from being withdrawn from said slot, the collar member being arranged such that the leading edge thereof can be withdrawn from the groove by moving the collar member along the sleeve in an axial direction away from the slot, so as to enable the anchoring device to be withdrawn from the slot.

In a preferred embodiment of the present invention, when said anchoring device is located within the slot, the leading edge of the collar member substantially fills the gap between the groove and the slot, said gap being created by the difference in their respective diameters.

The collar member is preferably substantially cylindrical and its leading edge is accordingly preferably substantially circular.

The slot is beneficially generally U-shaped and includes a narrowed neck portion, beneath which said leading edge of the collar member is engaged when the anchoring device is located within the slot. The leading edge beneficially includes a chamfer. The fixed member may also include at least one chamfer at the open edge thereof, the chamfer of the leading edge of the collar member and the at least one chamfer of the fixed member then preferably being arranged to cooperate with each other such that when the anchoring device is inserted in the slot, the fixed member chamfer operates to push the leading edge of the collar out of the groove and away from the fixed member.

The collar member is preferably spring biased in the direction of the fixed member, such that when the anchoring device is fully located within the slot, the leading edge of the collar member automatically extends into the groove. The collar member is then beneficially manually retractable against the spring force to withdraw the leading edge thereof from the groove, and enable the anchoring device to be withdrawn from the slot.

The anchoring device may include a load bearing ring surrounding at least a portion of the collar member. The device may further include a spring which is located underneath the collar member and is retained in compression by a cap member.

An embodiment of the present invention will now be described by way of example only and with reference to the accompanying drawings, in which:

Figure 1 is a perspective side view of an abutment according to an exemplary embodiment of the present invention;

Figure 2 is a perspective view of the abutment of Figure 1, a portion thereof being cut-away to illustrate the internal structure of the arrangement;

Figure 3 is a schematic section of the arrangement of Figure 1;

Figures 4 to 6 are schematic side views of an abutment according to an exemplary embodiment of the invention, at various stages of connection with the bracket; and

Figure 7 is a schematic, cross-sectional front view of the abutment of Figures 4 to 6 when connected to the bracket.

Referring to Figures 1 to 3 of the drawings, an abutment for anchoring an elongate member, for example, the sheath of a flexible cable, also known as a "push-pull" cable, is generally indicated at 10. In particular, the abutment 10 comprises a generally cylindrical body 12

having an axial through-cavity 14 along which a sliding core (not shown) of the push-pull cable is normally disposed.

Two cylindrical tubular portions 16a, 16b of smaller diameter than the body 12 extend at opposite ends of the body 12. Portion 16a guides the sliding of the inner core cable and an end rod (which prevents buckling of the inner core cable between a fixing point for the outer cable (non-movable) and a fixing point for the inner cable (movable)). Portion 16b is intended to fix the outer cable to the body 12.

The body 12 comprises a load bearing ring 7 defining two opposed shoulder portions 7a, 7b, the axial distance between which shoulder portions is fixed and defines an engagement portion of the abutment body 12. The abutment further comprises a spring loaded collar 1 having a chamfered end 9 including grooves 6 which allow it pass under the shoulder portion 7a of the load bearing ring 7 and into the engagement portion of abutment body 12. The spring 3 for operating the spring loaded collar 7 is located underneath the collar 7 and is retained in compression by a damper cap 4. As such, the spring force acts axially along the longitudinal axis of the body.

The abutment of this exemplary embodiment of the present invention is intended for use in anchoring a flexible cable to a bracket 8 defining a generally U-shaped seat 20. The upper edges of the bracket 8 are provided with a chamfered lead portion 22, the distance between the upper edges being less than the diameter of the seat 20 so as to define a neck 2. Further, the diameter of the engagement portion of the abutment is less than that of the U-shaped seat 20 of the bracket 8.

Referring in addition to Figures 4 to 7 of the drawings in use, when the abutment is presented to the bracket 8, the lead portions 22 of the bracket 8 picks up the corresponding chamfer 9 on the collar 1, causing the collar to slide backwards against the spring force and enabling the engagement portion of the abutment body to be located in the U-shaped seat 20 of the bracket 8. When the abutment is fully located in the seat 20, the spring 3 causes the collar 1 to be pushed toward the bracket, and the edge 9 of the collar 1 engages the bracket 8 under the neck

2. It will be appreciated that the collar 1 fills the space defined by the difference in diameters of the engagement portion of the abutment body and the seat 20 of the bracket 8.

The absence of a lead on the underside of the neck 2 in the bracket 8 means that the abutment remains firmly in place within the bracket 8. In order to remove the abutment from the bracket 8, the outside of the collar 1 is manually retracted against the spring force, thereby retracting the chamfered edge 9 of the collar 1 away from the seat 20 of the bracket 8 (and thus widening the opening) so as to enable the abutment to be withdrawn through the neck 2 of the bracket 8.

It will be appreciated that one of the main advantages of the abutment described above according to an exemplary embodiment of the present invention is its ability to be presented to the bracket from any angular orientation - there are no particular elements of the abutment and bracket which need to be matched or lined up. Further, the design achieves automatic firing, i.e. it automatically anchors itself within the bracket when it is fully located therein. The design provides positive location within the bracket, with an audible "click", so that an operative can be certain that the abutment has been correctly and completely located within the bracket. The abutment is easily removable from the bracket, and requires no re-arming before re-fitting. The arrangement also provides a clean external design.

A specific embodiment of an abutment according to the present invention has been described above by way of example only, and it will be appreciated by a person skilled in the art that modifications and variations can be made to the described embodiment without departing from the scope of the invention as defined by the appended claims.

Claims:

1. An anchoring device which is suitable for anchoring an elongate member to a fixed member having a slot leading to an edge thereof, the anchoring device comprising a sleeve which is fixable coaxially around said elongate member and which is provided with a peripheral groove, the axial length of which is sufficient to accommodate the thickness of the fixed member at said slot, the outer dimension of the groove being less than the inner dimension of the slot, the anchoring device further comprising a collar member which is carried by, and axially moveable along, said sleeve, said collar member having a leading edge which extends into said groove when the anchoring device is located within said slot, to effectively increase the dimension of said groove and prevent said anchoring device from being withdrawn from said slot, the collar member being arranged such that the leading edge thereof can be withdrawn from the groove by moving the collar member along the sleeve in an axial direction away from the slot, so as to enable the anchoring device to be withdrawn from the slot.
2. An anchoring device according to claim 1, wherein, when said anchoring device is located within said slot, the leading edge of said collar member substantially fills the gap between the groove and the slot, said gap being created by the difference in their respective dimensions.
3. An anchoring device according to claim 1 or claim 2, wherein said collar member is substantially cylindrical and said leading edge is substantially circular.
4. An anchoring device according to any one of the preceding claims, wherein said slot is generally U-shaped and includes a narrowed neck portion, beneath which said leading edge of the collar member is engaged when said anchoring device is located within said slot.

5. An anchoring device according to any one of the preceding claim, wherein said leading edge includes a chamfer.
6. An anchoring device according to claim 5, wherein said fixed member includes at least one chamfer at the open edge thereof, the chamfer of the leading edge of the collar member and the at least one chamfer of the fixed member being arranged to cooperate with each other such that when said anchoring device is inserted in said slot, the fixed member chamfer operates to push the leading edge of the collar out of the groove and away from the fixed member.
7. An anchoring device according to claim 6, wherein the collar member is spring biased in the direction of the fixed member, such that when the anchoring device is fully located within the slot, the leading edge of the collar member automatically extends into the groove.
8. An anchoring device according to claim 7, wherein said collar member is manually retractable against the spring force to withdraw the leading edge thereof from the groove, and enable the anchoring device to be withdrawn from the slot.
9. An anchoring device according to any one of the preceding claims, including a load bearing ring surrounding at least a portion of said collar member.
10. An anchoring device according to claim 7, including a spring located underneath said collar member and retained in compression by a cap member.
11. An anchoring device substantially as herein described with reference to the accompanying drawings.

ABSTRACT

Anchoring an Elongate Member

An anchoring device (10) for anchoring an elongate member to a fixed member (8), having a slot (20) leading to an edge thereof, the anchoring device comprising a sleeve (7) which is fixable coaxially around said elongate member and which is provided with a circumferential groove the axial length of which is sufficient to accommodate the thickness of the fixed member (8) at said slot (20), the outer diameter of the groove being less than the inner diameter of the slot (20), the anchoring device (10) further comprising a collar member (1) which is carried by, and axially moveable along, said sleeve, said collar member (1) having a leading edge (9) which extends into said groove when the anchoring device is located within said slot (20), to effectively increase the diameter of said groove and prevent said anchoring device from being withdrawn from said slot, the collar member (1) being arranged such that the leading edge (9) thereof can be withdrawn from the groove by moving the collar member along the sleeve in an axial direction away from the slot, so as to enable the anchoring device to be withdrawn from the slot.

[Figure 1]

1/4




FIG. 1

Perspective
View




FIG. 2

Sectional
View








Fig. 3



4/4



PCT Application
GB0304280



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.